

Subtype Loria 6006 R32

| | |
|---------------------|--|
| Certificate Holder | Groupe Atlantic |
| Address | 44 boulevard des Etats-Unis |
| ZIP | 85000 |
| City | La Roche Sur Yon |
| Country | FR |
| Certification Body | RISE CERT |
| Subtype title | Loria 6006 R32 |
| Registration number | 012-C700122 |
| Heat Pump Type | Outdoor Air/Water |
| Refrigerant | R32 |
| Mass of Refrigerant | 0.97 kg |
| Certification Date | 08.09.2021 |
| Testing basis | EN 14511:2018, EN 14825:2018, EN 12102:2017, EN 16147:2017 |

Model Loria 6006 R32

| | |
|-------------------------------------|-----------------------|
| Model name | Loria 6006 R32 |
| Application | Heating (medium temp) |
| Units | Indoor, Outdoor |
| Climate zone (for heating) | n/a |
| Cooling mode application (optional) | n/a |
| Any additional heat sources | n/a |

General data

| | |
|------------------|-------------|
| Power supply | 1x230V 50Hz |
| Off-peak product | n/a |

Outdoor Air/Water

EN 14511-4 | Heating

| | |
|--|--------|
| Shutting off the heat transfer medium flow | passed |
| Complete power supply failure | passed |
| Defrost test | passed |
| Starting and operating test | passed |

EN 12102-1 | Average Climate

| | Low temperature | Medium temperature |
|---------------------------|-----------------|--------------------|
| Sound power level indoor | 40 dB(A) | 40 dB(A) |
| Sound power level outdoor | 57 dB(A) | 57 dB(A) |

EN 14825 | Average Climate

| | Low temperature | Medium temperature |
|-----------------|-----------------|--------------------|
| η_s | 190 % | 132 % |
| Prated | 6.10 kW | 5.40 kW |
| SCOP | 4.82 | 3.37 |
| Tbiv | -7 °C | -7 °C |
| TOL | -10 °C | -10 °C |
| Pdh Tj = -7°C | 5.40 kW | 4.80 kW |
| COP Tj = -7°C | 2.97 | 2.08 |
| Cdh Tj = -7 °C | 0.990 | 0.990 |
| Pdh Tj = +2°C | 3.30 kW | 2.90 kW |
| COP Tj = +2°C | 4.64 | 3.22 |
| Cdh Tj = +2 °C | 0.980 | 0.990 |
| Pdh Tj = +7°C | 2.10 kW | 1.90 kW |
| COP Tj = +7°C | 6.67 | 4.62 |
| Cdh Tj = +7 °C | 0.960 | 0.970 |
| Pdh Tj = 12°C | 2.40 kW | 2.30 kW |
| COP Tj = 12°C | 8.34 | 6.57 |
| Cdh Tj = +12 °C | 0.960 | 0.960 |
| Pdh Tj = Tbiv | 5.40 kW | 4.80 kW |
| COP Tj = Tbiv | 2.97 | 2.08 |

| | | |
|---|-------------|-------------|
| Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh | 4.70 kW | 4.20 kW |
| COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh | 2.79 | 1.80 |
| Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh | 0.990 | 0.990 |
| WTOL | 55 °C | 55 °C |
| Poff | 4 W | 4 W |
| PTO | 12 W | 13 W |
| PSB | 10 W | 10 W |
| PCK | 0 W | 0 W |
| Supplementary Heater: Type of energy input | Electricity | Electricity |
| Supplementary Heater: PSUP | 1.40 kW | 1.20 kW |
| Annual energy consumption Qhe | 2614 kWh | 3307 kWh |

Model Loria Duo 6006 R32

| | |
|-------------------------------------|--------------------------|
| Model name | Loria Duo 6006 R32 |
| Application | Heating + DHW + low temp |
| Units | Indoor, Outdoor |
| Climate zone (for heating) | n/a |
| Cooling mode application (optional) | n/a |
| Any additional heat sources | n/a |

General data

| | |
|------------------|-----|
| Power supply | n/a |
| Off-peak product | n/a |

Outdoor Air/Water

EN 16147 | Average Climate

| | |
|---------------------------------|------------|
| Declared load profile | L |
| Efficiency η_{DHW} | 132 % |
| COP | 3.30 |
| Heating up time | 1:35 h:min |
| Standby power input | 31.0 W |
| Reference hot water temperature | 52.5 °C |
| Mixed water at 40°C | 245 l |

Model Loria Duo 6006 2C R32

| | |
|-------------------------------------|--------------------------|
| Model name | Loria Duo 6006 2C R32 |
| Application | Heating + DHW + low temp |
| Units | Indoor, Outdoor |
| Climate zone (for heating) | n/a |
| Cooling mode application (optional) | n/a |
| Any additional heat sources | n/a |

General data

| | |
|------------------|-------------|
| Power supply | 1x230V 50Hz |
| Off-peak product | n/a |

Outdoor Air/Water**EN 16147 | Average Climate**

| | |
|---------------------------------|------------|
| Declared load profile | L |
| Efficiency η_{DHW} | 132 % |
| COP | 3.30 |
| Heating up time | 1:35 h:min |
| Standby power input | 31.0 W |
| Reference hot water temperature | 52.5 °C |
| Mixed water at 40°C | 245 l |