

Subtype DAIKIN ALTHERMA 3 R F+W 08KW (180L)

Certificate Holder	DAIKIN Europe N.V.
Address	Zandvoordestraat 300
ZIP	B-8400
City	Oostende
Country	BE
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH
Subtype title	DAIKIN ALTHERMA 3 R F+W 08KW (180L)
Registration number	011-1W0221
Heat Pump Type	Outdoor Air/Water
Refrigerant	R32
Mass of Refrigerant	1.5 kg
Certification Date	22.11.2017
Testing basis	European KEYMARK Scheme for Heat Pumps Rev. 9 (as of 2021-03)

Model ERGA08EV / EHBH08E(6V/9W)

Model name	ERGA08EV / EHBH08E(6V/9W)
Application	Heating (medium temp)
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 14511-4 | Heating

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

EN 12102-1 | Average Climate

	Low temperature	Medium temperature
Sound power level indoor	42 dB(A)	42 dB(A)
Sound power level outdoor	62 dB(A)	62 dB(A)

EN 14825 | Average Climate

	Low temperature	Medium temperature
η_s	181 %	131 %
Prated	8 kW	8 kW
SCOP	4.61	3.35
Tbiv	-8 °C	-8 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	7 kW	6.9 kW
COP Tj = -7°C	2.77	1.96
Cdh Tj = -7 °C	1	
Pdh Tj = +2°C	4.2 kW	4.4 kW
COP Tj = +2°C	4.35	3.2
Cdh Tj = +2 °C	1	1
Pdh Tj = +7°C	3.3 kW	3.3 kW
COP Tj = +7°C	6.49	4.64
Cdh Tj = +7 °C	1	1
Pdh Tj = 12°C	3.9 kW	4.1 kW
COP Tj = 12°C	8.52	6.22
Cdh Tj = +12 °C	1	1
Pdh Tj = Tbiv	7.5 kW	7.5 kW
COP Tj = Tbiv	2.66	1.9

Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.9 kW	7.1 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.41	1.64
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1	1
WTOL	35 °C	55 °C
Poff	10 W	10 W
PTO	10 W	10 W
PSB	10 W	10 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.1 kW	0.9 kW
Annual energy consumption Qhe	3588 kWh	4939 kWh

Model ERGA08EV / EHBX08E(6V/9W)

Model name	ERGA08EV / EHBX08E(6V/9W)
Application	Heating (medium temp)
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 14511-4 | Heating

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

EN 12102-1 | Average Climate

	Low temperature	Medium temperature
Sound power level indoor	42 dB(A)	42 dB(A)
Sound power level outdoor	62 dB(A)	62 dB(A)

EN 14825 | Average Climate

	Low temperature	Medium temperature
η_s	181 %	131 %
Prated	8 kW	8 kW
SCOP	4.61	3.35
Tbiv	-8 °C	-8 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	7 kW	6.9 kW
COP Tj = -7°C	2.77	1.96
Cdh Tj = -7 °C	1	
Pdh Tj = +2°C	4.2 kW	4.4 kW
COP Tj = +2°C	4.35	3.2
Cdh Tj = +2 °C	1	1
Pdh Tj = +7°C	3.3 kW	3.3 kW
COP Tj = +7°C	6.49	4.64
Cdh Tj = +7 °C	1	1
Pdh Tj = 12°C	3.9 kW	4.1 kW
COP Tj = 12°C	8.52	6.22
Cdh Tj = +12 °C	1	1
Pdh Tj = Tbiv	7.5 kW	7.5 kW

COP Tj = Tbiv	2.66	1.9
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.9 kW	7.1 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.41	1.64
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1	1
WTOL	35 °C	55 °C
Poff	10 W	10 W
PTO	10 W	10 W
PSB	10 W	10 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.1 kW	0.9 kW
Annual energy consumption Qhe	3588 kWh	4939 kWh

Model ERGA08EV / EHVH08S18E(6V/9W)

Model name	ERGA08EV / EHVH08S18E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EV / EHVX08S18E6V(G)

Model name	ERGA08EV / EHVX08S18E6V(G)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EV / EHVX08S18E9W

Model name	ERGA08EV / EHVX08S18E9W
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EV / EHVZ08S18E(6V/9W)

Model name	ERGA08EV / EHVZ08S18E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EV / EHVH08SU18E6V

Model name	ERGA08EV / EHVH08SU18E6V
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EV / EHBH08E(6V/9W) + cooling kit

Model name	ERGA08EV / EHBH08E(6V/9W) + cooling kit
Application	Heating (medium temp)
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 14511-4 | Heating

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

EN 12102-1 | Average Climate

	Low temperature	Medium temperature
Sound power level indoor	42 dB(A)	42 dB(A)
Sound power level outdoor	62 dB(A)	62 dB(A)

EN 14825 | Average Climate

	Low temperature	Medium temperature
η_s	181 %	131 %
Prated	8 kW	8 kW
SCOP	4.61	3.35
Tbiv	-8 °C	-8 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	7 kW	6.9 kW
COP Tj = -7°C	2.77	1.96
Cdh Tj = -7 °C	1	
Pdh Tj = +2°C	4.2 kW	4.4 kW
COP Tj = +2°C	4.35	3.2
Cdh Tj = +2 °C	1	1
Pdh Tj = +7°C	3.3 kW	3.3 kW
COP Tj = +7°C	6.49	4.64
Cdh Tj = +7 °C	1	1
Pdh Tj = 12°C	3.9 kW	4.1 kW
COP Tj = 12°C	8.52	6.22
Cdh Tj = +12 °C	1	1
Pdh Tj = Tbiv	7.5 kW	7.5 kW

COP Tj = Tbiv	2.66	1.9
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.9 kW	7.1 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.41	1.64
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1	1
WTOL	35 °C	55 °C
Poff	10 W	10 W
PTO	10 W	10 W
PSB	10 W	10 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.1 kW	0.9 kW
Annual energy consumption Qhe	3588 kWh	4939 kWh

Model ERGA08EV / EHVH08S18E(6V/9W) + cooling kit

Model name	ERGA08EV / EHVH08S18E(6V/9W) + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EV / EHVZ08S18E(6V/9W) + cooling kit

Model name	ERGA08EV / EHVZ08S18E(6V/9W) + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EVH / EHBH08E(6V/9W)

Model name	ERGA08EVH / EHBH08E(6V/9W)
Application	Heating (medium temp)
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 14511-4 | Heating

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

EN 12102-1 | Average Climate

	Low temperature	Medium temperature
Sound power level indoor	42 dB(A)	42 dB(A)
Sound power level outdoor	62 dB(A)	62 dB(A)

EN 14825 | Average Climate

	Low temperature	Medium temperature
η_s	179 %	130 %
Prated	8 kW	8 kW
SCOP	4.56	3.32
Tbiv	-8 °C	-8 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	7 kW	6.9 kW
COP Tj = -7°C	2.77	1.96
Cdh Tj = -7 °C	1	
Pdh Tj = +2°C	4.2 kW	4.4 kW
COP Tj = +2°C	4.35	3.2
Cdh Tj = +2 °C	1	1
Pdh Tj = +7°C	3.3 kW	3.3 kW
COP Tj = +7°C	6.49	4.64
Cdh Tj = +7 °C	1	1
Pdh Tj = 12°C	3.9 kW	4.1 kW
COP Tj = 12°C	8.52	6.22
Cdh Tj = +12 °C	1	1
Pdh Tj = Tbiv	7.5 kW	7.5 kW
COP Tj = Tbiv	2.66	1.9

Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.9 kW	7.1 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.41	1.64
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1	1
WTOL	35 °C	55 °C
Poff	10 W	10 W
PTO	10 W	10 W
PSB	10 W	10 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.1 kW	0.9 kW
Annual energy consumption Qhe	3625 kWh	4975 kWh

Model ERGA08EVH / EHBX08E(6V/9W)

Model name	ERGA08EVH / EHBX08E(6V/9W)
Application	Heating (medium temp)
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 14511-4 | Heating

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

EN 12102-1 | Average Climate

	Low temperature	Medium temperature
Sound power level indoor	42 dB(A)	42 dB(A)
Sound power level outdoor	62 dB(A)	62 dB(A)

EN 14825 | Average Climate

	Low temperature	Medium temperature
η_s	181 %	131 %
Prated	8 kW	8 kW
SCOP	4.61	3.35
Tbiv	-8 °C	-8 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	7 kW	6.9 kW
COP Tj = -7°C	2.77	1.96
Cdh Tj = -7 °C	1	
Pdh Tj = +2°C	4.2 kW	4.4 kW
COP Tj = +2°C	4.35	3.2
Cdh Tj = +2 °C	1	1
Pdh Tj = +7°C	3.3 kW	3.3 kW
COP Tj = +7°C	6.49	4.64
Cdh Tj = +7 °C	1	1
Pdh Tj = 12°C	3.9 kW	4.1 kW
COP Tj = 12°C	8.52	6.22
Cdh Tj = +12 °C	1	1
Pdh Tj = Tbiv	7.5 kW	7.5 kW

COP Tj = Tbiv	2.66	1.9
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.9 kW	7.1 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.41	1.64
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1	1
WTOL	35 °C	55 °C
Poff	10 W	10 W
PTO	10 W	10 W
PSB	10 W	10 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.1 kW	0.9 kW
Annual energy consumption Qhe	3588 kWh	4939 kWh

Model ERGA08EVH / EHVH08S18E(6V/9W)

Model name	ERGA08EVH / EHVH08S18E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EVH / EHVX08S18E(6V/9W)

Model name	ERGA08EVH / EHVX08S18E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EVH / EHVZ08S18E(6V/9W)

Model name	ERGA08EVH / EHVZ08S18E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EVH / EHVH08SU18E6V

Model name	ERGA08EVH / EHVH08SU18E6V
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EVH / EHBH08E(6V/9W) + cooling kit

Model name	ERGA08EVH / EHBH08E(6V/9W) + cooling kit
Application	Heating (medium temp)
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 14511-4 | Heating

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

EN 12102-1 | Average Climate

	Low temperature	Medium temperature
Sound power level indoor	42 dB(A)	42 dB(A)
Sound power level outdoor	62 dB(A)	62 dB(A)

EN 14825 | Average Climate

	Low temperature	Medium temperature
η_s	181 %	131 %
Prated	8 kW	8 kW
SCOP	4.61	3.35
Tbiv	-8 °C	-8 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	7 kW	6.9 kW
COP Tj = -7°C	2.77	1.96
Cdh Tj = -7 °C	1	
Pdh Tj = +2°C	4.2 kW	4.4 kW
COP Tj = +2°C	4.35	3.2
Cdh Tj = +2 °C	1	1
Pdh Tj = +7°C	3.3 kW	3.3 kW
COP Tj = +7°C	6.49	4.64
Cdh Tj = +7 °C	1	1
Pdh Tj = 12°C	3.9 kW	4.1 kW
COP Tj = 12°C	8.52	6.22
Cdh Tj = +12 °C	1	1
Pdh Tj = Tbiv	7.5 kW	7.5 kW

COP $T_j = T_{biv}$	2.66	1.9
$P_{dh} T_j = TOL$ or $P_{dh} T_j = T_{designh}$ if $TOL < T_{designh}$	6.9 kW	7.1 kW
COP $T_j = TOL$ or COP $T_j = T_{designh}$ if $TOL < T_{designh}$	2.41	1.64
$C_{dh} T_j = TOL$ or $P_{dh} T_j = T_{designh}$ if $TOL < T_{designh}$	1	1
WTOL	35 °C	55 °C
P _{off}	10 W	10 W
PTO	10 W	10 W
PSB	10 W	10 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.1 kW	0.9 kW
Annual energy consumption Q _{he}	3588 kWh	4939 kWh

Model ERGA08EVH / EHVH08S18E(6V/9W) + cooling kit

Model name	ERGA08EVH / EHVH08S18E(6V/9W) + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EVH / EHVZ08S18E(6V/9W) + cooling kit

Model name	ERGA08EVH / EHVZ08S18E(6V/9W) + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EVH7 / EHBH08E(6V/9W)

Model name	ERGA08EVH7 / EHBH08E(6V/9W)
Application	Heating (medium temp)
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 14511-4 | Heating

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

EN 12102-1 | Average Climate

	Low temperature	Medium temperature
Sound power level indoor	42 dB(A)	42 dB(A)
Sound power level outdoor	62 dB(A)	62 dB(A)

EN 14825 | Average Climate

	Low temperature	Medium temperature
η_s	179 %	130 %
Prated	8 kW	8 kW
SCOP	4.56	3.32
Tbiv	-8 °C	-8 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	7 kW	6.9 kW
COP Tj = -7°C	2.77	1.96
Cdh Tj = -7 °C	1	
Pdh Tj = +2°C	4.2 kW	4.4 kW
COP Tj = +2°C	4.35	3.2
Cdh Tj = +2 °C	1	1
Pdh Tj = +7°C	3.3 kW	3.3 kW
COP Tj = +7°C	6.49	4.64
Cdh Tj = +7 °C	1	1
Pdh Tj = 12°C	3.9 kW	4.1 kW
COP Tj = 12°C	8.52	6.22
Cdh Tj = +12 °C	1	1
Pdh Tj = Tbiv	7.5 kW	7.5 kW
COP Tj = Tbiv	2.66	1.9

Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.9 kW	7.1 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.41	1.64
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1	1
WTOL	35 °C	55 °C
Poff	10 W	10 W
PTO	10 W	10 W
PSB	10 W	10 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.1 kW	0.9 kW
Annual energy consumption Qhe	3,625 kWh	4,975 kWh

Model ERGA08EVH7 / EHBX08E(6V/9W)

Model name	ERGA08EVH7 / EHBX08E(6V/9W)
Application	Heating (medium temp)
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 14511-4 | Heating

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

EN 12102-1 | Average Climate

	Low temperature	Medium temperature
Sound power level indoor	42 dB(A)	42 dB(A)
Sound power level outdoor	62 dB(A)	62 dB(A)

EN 14825 | Average Climate

	Low temperature	Medium temperature
η_s	181 %	131 %
Prated	8 kW	8 kW
SCOP	4.61	3.35
Tbiv	-8 °C	-8 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	7 kW	6.9 kW
COP Tj = -7°C	2.77	1.96
Cdh Tj = -7 °C	1	
Pdh Tj = +2°C	4.2 kW	4.4 kW
COP Tj = +2°C	4.35	3.2
Cdh Tj = +2 °C	1	1
Pdh Tj = +7°C	3.3 kW	3.3 kW
COP Tj = +7°C	6.49	4.64
Cdh Tj = +7 °C	1	1
Pdh Tj = 12°C	3.9 kW	4.1 kW
COP Tj = 12°C	8.52	6.22
Cdh Tj = +12 °C	1	1
Pdh Tj = Tbiv	7.5 kW	7.5 kW

COP Tj = Tbiv	2.66	1.9
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.9 kW	7.1 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.41	1.64
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	1	1
WTOL	35 °C	55 °C
Poff	10 W	10 W
PTO	10 W	10 W
PSB	10 W	10 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.1 kW	0.9 kW
Annual energy consumption Qhe	3,588 kWh	4,939 kWh

Model ERGA08EVH7 / EHVH08S18E(6V/9W)

Model name	ERGA08EVH7 / EHVH08S18E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EVH7 / EHVX08S18E(6V/9W)

Model name	ERGA08EVH7 / EHVX08S18E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EVH7 / EHVZ08S18E(6V/9W)

Model name	ERGA08EVH7 / EHVZ08S18E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EVH7 / EHVH08SU18E6V

Model name	ERGA08EVH7 / EHVH08SU18E6V
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EVH7 / EHBH08E(6V/9W) + cooling kit

Model name	ERGA08EVH7 / EHBH08E(6V/9W) + cooling kit
Application	Heating (medium temp)
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 14511-4 | Heating

Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

EN 12102-1 | Average Climate

	Low temperature	Medium temperature
Sound power level indoor	42 dB(A)	42 dB(A)
Sound power level outdoor	62 dB(A)	62 dB(A)

EN 14825 | Average Climate

	Low temperature	Medium temperature
η_s	181 %	131 %
Prated	8 kW	8 kW
SCOP	4.61	3.35
Tbiv	-8 °C	-8 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	7 kW	6.9 kW
COP Tj = -7°C	2.77	1.96
Cdh Tj = -7 °C	1	
Pdh Tj = +2°C	4.2 kW	4.4 kW
COP Tj = +2°C	4.35	3.2
Cdh Tj = +2 °C	1	1
Pdh Tj = +7°C	3.3 kW	3.3 kW
COP Tj = +7°C	6.49	4.64
Cdh Tj = +7 °C	1	1
Pdh Tj = 12°C	3.9 kW	4.1 kW
COP Tj = 12°C	8.52	6.22
Cdh Tj = +12 °C	1	1
Pdh Tj = Tbiv	7.5 kW	7.5 kW

COP $T_j = T_{biv}$	2.66	1.9
$P_{dh} T_j = TOL$ or $P_{dh} T_j = T_{designh}$ if $TOL < T_{designh}$	6.9 kW	7.1 kW
COP $T_j = TOL$ or COP $T_j = T_{designh}$ if $TOL < T_{designh}$	2.41	1.64
$C_{dh} T_j = TOL$ or $P_{dh} T_j = T_{designh}$ if $TOL < T_{designh}$	1	1
WTOL	35 °C	55 °C
P _{off}	10 W	10 W
PTO	10 W	10 W
PSB	10 W	10 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.1 kW	0.9 kW
Annual energy consumption Q _{he}	3,588 kWh	4,939 kWh

Model ERGA08EVH7 / EHVH08S18E(6V/9W) + cooling kit

Model name	ERGA08EVH7 / EHVH08S18E(6V/9W) + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l

Model ERGA08EVH7 / EHVZ08S18E(6V/9W) + cooling kit

Model name	ERGA08EVH7 / EHVZ08S18E(6V/9W) + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	125 %
COP	3.1
Heating up time	1:40 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	238 l