

Subtype WWK 301 electronic

Certificate Holder	STIEBEL ELTRON GmbH & Co KG
Address	Dr. Stiebel Straße 33
ZIP	37603
City	Holzminden
Country	DE
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH
Subtype title	WWK 301 electronic
Registration number	011-1W0115
Heat Pump Type	Heat Pump for Domestic Hot Water (DHW)
Refrigerant	R134a
Mass of Refrigerant	0.85 kg



Model WWK 301 electronic	
Model name	WWK 301 electronic
Application	Heating + DHW
Units	Indoor
Climate zone (for heating)	Warmer Climate, Colder Climate
Cooling mode application (optional)	n/a
Any additional heat sources	n/a
General data	
Power supply	1x230V 50Hz
Off-peak product	No
Heat Pump for Domestic Hot Water (DHW) EN 12102-2 Average Climate	
Sound power level indoor	60 dB(A)
EN 16147 Average Climate	
Declared load profile	XL
	XL 154 %
Declared load profile	
Declared load profile Efficiency ηDHW	154 %
Declared load profile Efficiency ηDHW COP Heating up time Standby power input	154 % 3.75 9:16 h:min 58.0 W
Declared load profile Efficiency ηDHW COP Heating up time	154 % 3.75 9:16 h:min



Model WWK 301 electronic	
Model name	WWK 301 electronic
Application	Heating + DHW
Units	Indoor, Outdoor
Climate zone (for heating)	Warmer Climate, Colder Climate
Cooling mode application (optional)	n/a
Any additional heat sources	n/a
General data	
Power supply	1x230V 50Hz
Off-peak product	No
Heat Pump for Domestic Hot Water (DHW	/)
EN 12102-2 Average Climate	
EN 12102-2 Average Climate Sound power level indoor	52 dB(A)
	52 dB(A) 48 dB(A)
Sound power level indoor	
Sound power level indoor Sound power level outdoor	
Sound power level indoor Sound power level outdoor EN 16147 Average Climate	48 dB(A)
Sound power level indoor Sound power level outdoor EN 16147 Average Climate Declared load profile Efficiency ηDHW COP	48 dB(A) XL 132 % 3.22
Sound power level indoor Sound power level outdoor EN 16147 Average Climate Declared load profile Efficiency nDHW COP Heating up time	48 dB(A) XL 132 % 3.22 11:19 h:min
Sound power level indoor Sound power level outdoor EN 16147 Average Climate Declared load profile Efficiency nDHW COP Heating up time Standby power input	48 dB(A) XL 132 % 3.22 11:19 h:min 68.0 W
Sound power level indoor Sound power level outdoor EN 16147 Average Climate Declared load profile Efficiency nDHW COP Heating up time	48 dB(A) XL 132 % 3.22 11:19 h:min



Model name	WWK 301 electronic SOL
Application	Heating + DHW
Units	Indoor
Climate zone (for heating)	Warmer Climate, Colder Climate
Cooling mode application (optional)	n/a
Any additional heat sources	n/a
General data	
Power supply	1x230V 50Hz
Off-peak product	No
Heat Pump for Domestic Hot Water (DHW)	
EN 12102-2 Average Climate	
EN 12102-2 Average Climate Sound power level indoor	60 dB(A)
	60 dB(A)
Sound power level indoor	60 dB(A) XL
Sound power level indoor EN 16147 Average Climate	
Sound power level indoor EN 16147 Average Climate Declared load profile	XL
Sound power level indoor EN 16147 Average Climate Declared load profile Efficiency nDHW	XL 154 %
Sound power level indoor EN 16147 Average Climate Declared load profile Efficiency nDHW COP	XL 154 % 3.75
Sound power level indoor EN 16147 Average Climate Declared load profile Efficiency nDHW COP Heating up time	XL 154 % 3.75 9:16 h:min



Model WWK 301 electronic SOL	
Model name	WWK 301 electronic SOL
Application	Heating + DHW
Units	Indoor, Outdoor
Climate zone (for heating)	Warmer Climate, Colder Climate
Cooling mode application (optional)	n/a
Any additional heat sources	n/a
General data	
Power supply	1x230V 50Hz
Off-peak product	No
Heat Pump for Domestic Hot Water (DHW) EN 12102-2 Average Climate	
Sound power level indoor	52 dB(A)
	52 dB(A) 48 dB(A)
Sound power level indoor	
Sound power level indoor Sound power level outdoor	
Sound power level indoor Sound power level outdoor EN 16147 Average Climate	48 dB(A)
Sound power level indoor Sound power level outdoor EN 16147 Average Climate Declared load profile	48 dB(A) XL
Sound power level indoor Sound power level outdoor EN 16147 Average Climate Declared load profile Efficiency nDHW	48 dB(A) XL 122 %
Sound power level indoor Sound power level outdoor EN 16147 Average Climate Declared load profile Efficiency nDHW COP	48 dB(A) XL 122 % 2.99
Sound power level indoor Sound power level outdoor EN 16147 Average Climate Declared load profile Efficiency nDHW COP Heating up time	48 dB(A) XL 122 % 2.99 12:14 h:min