

Subtype DC Inverter Heat Pump 120		
Certificate Holder	GZ Dotels Electric Appliances Co., Ltd.	
Address	No.B23, Huachuang Animation Industrial Park	
ZIP		
City	Guangzhou	
Country	CN	
Certification Body	BRE Global Limited	
Subtype title	DC Inverter Heat Pump 120	
Registration number	041-K030-03	
Heat Pump Type	Outdoor Air/Water	
Refrigerant	R32	
Mass of Refrigerant	1.75 kg	
Certification Date	14.11.2022	
Testing basis	Heat Pump Keymark Scheme Rules Rev 11	



Model	KS-120W	/EN8RP
Model	KJ-IZUVV	

Model name	KS-120W/EN8BP		
Application	Heating (medium temp)		
Units	Outdoor		
Climate zone (for heating)	n/a		
Reversibility	Yes		
Cooling mode application (optional)	n/a		
Any additional heat sources	n/a		
General data			
Power supply	1x230V 50Hz		
Off-peak product	n/a		
Outdoor Air/Water			
EN 14511-4   Heating			
Shutting off the heat transfer medium flow	passed		
Complete power supply failure	passed		
Defrost test	passed		
Starting and operating test	passed		
EN 12102-1   Average Climate			
	Low temperature	Medium temperature	
Sound power level outdoor	60 dB(A)	64 dB(A)	
EN 14825   Average Climate			
	Low temperature	Medium temperature	
ηs	180 %	132 %	
Prated	11.28 kW	11.08 kW	
SCOP	4.56	3.37	
Tbiv	-7 °C	-7 °C	
	-7 °C -10 °C		
Tbiv TOL Pdh Tj = -7°C		-7 °C	
TOL	-10 °C	-7 °C -10 °C	
TOL Pdh Tj = -7°C	-10 °C 9.98 kW	-7 °C -10 °C 9.80 kW	
TOL Pdh Tj = -7°C COP Tj = -7°C	-10 °C 9.98 kW 2.54	-7 °C -10 °C 9.80 kW 2.00	
TOL Pdh Tj = $-7^{\circ}$ C COP Tj = $-7^{\circ}$ C Cdh Tj = $-7^{\circ}$ C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C	-10 °C 9.98 kW 2.54 0.990	-7 °C -10 °C 9.80 kW 2.00 0.990	
TOL Pdh Tj = $-7^{\circ}$ C COP Tj = $-7^{\circ}$ C Cdh Tj = $-7^{\circ}$ C Pdh Tj = $+2^{\circ}$ C	-10 °C 9.98 kW 2.54 0.990 6.30 kW	-7 °C -10 °C 9.80 kW 2.00 0.990 6.58 kW	
TOL Pdh Tj = $-7^{\circ}$ C COP Tj = $-7^{\circ}$ C Cdh Tj = $-7^{\circ}$ C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C	-10 °C 9.98 kW 2.54 0.990 6.30 kW 4.42	-7 °C -10 °C 9.80 kW 2.00 0.990 6.58 kW 3.27	
TOL Pdh Tj = $-7^{\circ}$ C COP Tj = $-7^{\circ}$ C Cdh Tj = $-7^{\circ}$ C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C	-10 °C 9.98 kW 2.54 0.990 6.30 kW 4.42 0.990	-7 °C -10 °C 9.80 kW 2.00 0.990 6.58 kW 3.27 0.990	
TOL Pdh Tj = $-7^{\circ}$ C COP Tj = $-7^{\circ}$ C Cdh Tj = $-7^{\circ}$ C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C	-10 °C 9.98 kW 2.54 0.990 6.30 kW 4.42 0.990 4.30 kW	-7 °C -10 °C 9.80 kW 2.00 0.990 6.58 kW 3.27 0.990 4.24 kW	
TOL Pdh Tj = $-7^{\circ}$ C COP Tj = $-7^{\circ}$ C Cdh Tj = $-7^{\circ}$ C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C	-10 °C 9.98 kW 2.54 0.990 6.30 kW 4.42 0.990 4.30 kW 6.33	-7 °C -10 °C 9.80 kW 2.00 0.990 6.58 kW 3.27 0.990 4.24 kW 4.45	
TOL Pdh Tj = $-7^{\circ}$ C COP Tj = $-7^{\circ}$ C Cdh Tj = $-7^{\circ}$ C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C	-10 °C 9.98 kW 2.54 0.990 6.30 kW 4.42 0.990 4.30 kW 6.33 0.990	-7 °C -10 °C 9.80 kW 2.00 0.990 6.58 kW 3.27 0.990 4.24 kW 4.45 0.990	
TOL Pdh Tj = $-7^{\circ}$ C COP Tj = $-7^{\circ}$ C Pdh Tj = $-7^{\circ}$ C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C Pdh Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C Pdh Tj = $+7^{\circ}$ C Pdh Tj = $+7^{\circ}$ C	-10 °C 9.98 kW 2.54 0.990 6.30 kW 4.42 0.990 4.30 kW 6.33 0.990 4.32 kW	-7 °C -10 °C 9.80 kW 2.00 0.990 6.58 kW 3.27 0.990 4.24 kW 4.45 0.990 5.00 kW	
TOL Pdh Tj = $-7^{\circ}$ C COP Tj = $-7^{\circ}$ C Cdh Tj = $-7^{\circ}$ C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C Cdh Tj = $+7^{\circ}$ C Pdh Tj = $12^{\circ}$ C Pdh Tj = $12^{\circ}$ C	-10 °C 9.98 kW 2.54 0.990 6.30 kW 4.42 0.990 4.30 kW 6.33 0.990 4.32 kW 8.88	-7 °C -10 °C 9.80 kW 2.00 0.990 6.58 kW 3.27 0.990 4.24 kW 4.45 0.990 5.00 kW 6.54	



Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	10.02 kW	9.03 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.40	1.80
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.990	0.990
WTOL	67 °C	67 °C
Poff	7 W	7 W
РТО	19 W	19 W
PSB	7 W	7 W
РСК	17 W	17 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.26 kW	2.05 kW
Annual energy consumption Qhe	5112 kWh	6791 kWh