

Subtype Chappée ERIA S PLUS DUO R32 4-6

Certificate Holder	BDR Thermea FR (CHAPPEE)
Address	57 rue de la Gare
ZIP	67580
City	Mertzwiller
Country	FR
Certification Body	Kiwa Nederland B.V.
Subtype title	Chappée ERIA S PLUS DUO R32 4-6
Registration number	22HK0033/00
Heat Pump Type	Outdoor Air/Water
Refrigerant	R32
Mass of Refrigerant	1.5 kg
Certification Date	11.11.2022
Testing basis	European KEYMARK Scheme for Heat Pumps (v10)

Model ERIA S PLUS DUO R32 4 MR/EM

Model name	ERIA S PLUS DUO R32 4 MR/EM
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C, +18°C/+23°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water**EN 16147 | Average Climate**

Declared load profile	L
Efficiency η_{DHW}	131 %
COP	3.14
Heating up time	1:35 h:min
Standby power input	28.5 W
Reference hot water temperature	53.0 °C
Mixed water at 40°C	240 l

Model ERIA S PLUS DUO R32 6 MR/EM

Model name	ERIA S PLUS DUO R32 6 MR/EM
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C, +18°C/+23°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	131 %
COP	3.14
Heating up time	1:35 h:min
Standby power input	28.5 W
Reference hot water temperature	53.0 °C
Mixed water at 40°C	240 l

Model ERIA S PLUS DUO R32 4 MR/H

Model name	ERIA S PLUS DUO R32 4 MR/H
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C, +18°C/+23°C
Any additional heat sources	n/a

General data

Power supply	n/a
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	131 %
COP	3.14
Heating up time	1:35 h:min
Standby power input	28.5 W
Reference hot water temperature	53.0 °C
Mixed water at 40°C	240 l

Model ERIA S PLUS DUO R32 6 MR/H

Model name	ERIA S PLUS DUO R32 6 MR/H
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C, +18°C/+23°C
Any additional heat sources	n/a

General data

Power supply	n/a
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	131 %
COP	3.14
Heating up time	1:35 h:min
Standby power input	28.5 W
Reference hot water temperature	53.0 °C
Mixed water at 40°C	240 l