

## Subtype DAITSU SPLIT URBAN 22 30

Certificate Holder	Eurofred S.A.
Address	Marqués de Sentmenat, 97
ZIP	08029
City	Barcelona
Country	ES
Certification Body	BRE Global Limited
Subtype title	DAITSU SPLIT URBAN 22 30
Registration number	041-K010-09
Heat Pump Type	Outdoor Air/Water
Refrigerant	R32
Mass of Refrigerant	1.1 kg
Certification Date	08.03.2021
Testing basis	Heat Pump Keymark Scheme Rules Rev 09

## Model SPLIT URBAN AOWD 22

Model name	SPLIT URBAN AOWD 22
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	Colder, Warmer, Warmer Climate, Colder Climate
Reversibility	Yes
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

## General data

Power supply	1x230V 50Hz
Off-peak product	n/a

## Outdoor Air/Water

### EN 16147 | Average Climate

Declared load profile	L
Efficiency $\eta_{DHW}$	123 %
COP	2.92
Heating up time	1:47 h:min
Standby power input	36.1 W
Reference hot water temperature	53.1 °C
Mixed water at 40°C	226 l

### EN 16147 | Colder Climate

Declared load profile	L
Efficiency $\eta_{DHW}$	94 %
COP	2.25
Heating up time	1:58 h:min
Standby power input	38.2 W
Reference hot water temperature	53.0 °C
Mixed water at 40°C	226 l

### EN 16147 | Warmer Climate

Declared load profile	L
Efficiency $\eta_{DHW}$	143 %
COP	3.40
Heating up time	1:33 h:min
Standby power input	30.0 W
Reference hot water temperature	53.2 °C
Mixed water at 40°C	226 l

## Model SPLIT URBAN AOWD 30

Model name	SPLIT URBAN AOWD 30
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	Colder, Warmer, Warmer Climate, Colder Climate
Reversibility	Yes
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

## General data

Power supply	1x230V 50Hz
Off-peak product	n/a

## Outdoor Air/Water

### EN 16147 | Average Climate

Declared load profile	L
Efficiency $\eta_{DHW}$	123 %
COP	2.92
Heating up time	1:47 h:min
Standby power input	36.1 W
Reference hot water temperature	53.1 °C
Mixed water at 40°C	226 l

### EN 16147 | Colder Climate

Declared load profile	L
Efficiency $\eta_{DHW}$	94 %
COP	2.25
Heating up time	1:58 h:min
Standby power input	38.2 W
Reference hot water temperature	53.0 °C
Mixed water at 40°C	226 l

### EN 16147 | Warmer Climate

Declared load profile	L
Efficiency $\eta_{DHW}$	143 %
COP	3.40
Heating up time	1:33 h:min
Standby power input	30.0 W
Reference hot water temperature	53.2 °C
Mixed water at 40°C	226 l