

Subtype DC Inverter Air to Water Heat Pump Unit- R290- 06- C

Certificate Holder	Zhongshan Amitime Electric Co., Ltd
Address	5th Yandong Rd
ZIP	
City	Zhongshan City - Guangdong
Country	CN
Certification Body	BRE Global Limited
Subtype title	DC Inverter Air to Water Heat Pump Unit- R290- 06- C
Registration number	041-K027-13
Heat Pump Type	Outdoor Air/Water
Refrigerant	R290
Mass of Refrigerant	0.6 kg
Certification Date	22.09.2023
Testing basis	Heat Pump Keymark Scheme Rules Rev 12

Model Indoor unit: PAVH-06-20V1GX-250L/IX, Outdoor unit: PAVH-06V1GXX

Model name	Indoor unit: PAVH-06-20V1GX-250L/IX, Outdoor unit: PAVH-06V1GXX
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Reversibility	Yes
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	No

Outdoor Air/Water

EN 16147 | Operating test

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

EN 12102-2 | Average Climate

Sound power level indoor	37 dB(A)
Sound power level outdoor	57 dB(A)

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	124 %
COP	2.99
Heating up time	43:16:40 h:min
Standby power input	24.0 W
Reference hot water temperature	45.2 °C
Mixed water at 40°C	222 l

Model Indoor unit: ecoSTAR All-in-one, Outdoor unit: ecoSTAR06

Model name	Indoor unit: ecoSTAR All-in-one, Outdoor unit: ecoSTAR06
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Operating test

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

EN 12102-2 | Average Climate

Sound power level indoor	37 dB(A)
Sound power level outdoor	57 dB(A)

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	124 %
COP	2.99
Heating up time	43:16:40 h:min
Standby power input	24.0 W
Reference hot water temperature	45.2 °C
Mixed water at 40°C	222 l