

Subtype DAIKIN ALTHERMA 3 R F 08KW (230L)

Certificate Holder	DAIKIN Europe N.V.
Address	Zandvoordestraat 300
ZIP	B-8400
City	Oostende
Country	BE
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH
Subtype title	DAIKIN ALTHERMA 3 R F 08KW (230L)
Registration number	011-1W0222
Heat Pump Type	Outdoor Air/Water
Refrigerant	R32
Mass of Refrigerant	1.5 kg
Certification Date	22.11.2017
Testing basis	European KEYMARK Scheme for Heat Pumps Rev. 9 (as of 2021-03)

Model ERGA08EV / EHVH08S23E(6V/9W)

Model name	ERGA08EV / EHVH08S23E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EV / EHVX08S23E6V(G)

Model name	ERGA08EV / EHVX08S23E6V(G)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EV / EHVX08S23E9W

Model name	ERGA08EV / EHVX08S23E9W
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EV / EHVZ08S23E(6V/9W)

Model name	ERGA08EV / EHVZ08S23E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water**EN 16147 | Average Climate**

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EV / EHVH08SU23E6V

Model name	ERGA08EV / EHVH08SU23E6V
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EV / EHVH08S23E(6V/9W) + cooling kit

Model name	ERGA08EV / EHVH08S23E(6V/9W) + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EV / EHVZ08S23E(6V/9W) + cooling kit

Model name	ERGA08EV / EHVZ08S23E(6V/9W) + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EVH / EHVH08S23E(6V/9W)

Model name	ERGA08EVH / EHVH08S23E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EVH / EHVX08S23E(6V/9W)

Model name	ERGA08EVH / EHVX08S23E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EVH / EHVZ08S23E(6V/9W)

Model name	ERGA08EVH / EHVZ08S23E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EVH / EHVH08SU23E6V

Model name	ERGA08EVH / EHVH08SU23E6V
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EVH / EHVH08S23E(6V/9W) + cooling kit

Model name	ERGA08EVH / EHVH08S23E(6V/9W) + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EVH / EHVZ08S23E(6V/9W) + cooling kit

Model name	ERGA08EVH / EHVZ08S23E(6V/9W) + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EVH7 / EHVH08S23E(6V/9W)

Model name	ERGA08EVH7 / EHVH08S23E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EVH7 / EHVX08S23E(6V/9W)

Model name	ERGA08EVH7 / EHVX08S23E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EVH7 / EHVZ08S23E(6V/9W)

Model name	ERGA08EVH7 / EHVZ08S23E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EVH7 / EHVH08SU23E6V

Model name	ERGA08EVH7 / EHVH08SU23E6V
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EVH7 / EHVH08S23E(6V/9W) + cooling kit

Model name	ERGA08EVH7 / EHVH08S23E(6V/9W) + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l

Model ERGA08EVH7 / EHVZ08S23E(6V/9W) + cooling kit

Model name	ERGA08EVH7 / EHVZ08S23E(6V/9W) + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	133 %
COP	3.3
Heating up time	1:47 h:min
Standby power input	28 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	288 l