

Subtype DAIKIN ALTHERMA 3 R F 3.5KW

Certificate Holder	DAIKIN Europe N.V.
Address	Zandvoordestraat 300
ZIP	B-8400
City	Oostende
Country	BE
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH
Subtype title	DAIKIN ALTHERMA 3 R F 3.5KW
Registration number	011-1W0198
Heat Pump Type	Outdoor Air/Water
Refrigerant	R32
Mass of Refrigerant	1 kg
Certification Date	27.03.2020
Testing basis	European KEYMARK Scheme for Heat Pumps Rev.10

Model ERLA03DV / EHFH03S18D3V

Model name	ERLA03DV / EHFH03S18D3V
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	110 %
COP	2.67
Heating up time	1:40 h:min
Standby power input	19 W
Reference hot water temperature	52.7 °C
Mixed water at 40°C	240 l

Model ERLA03DV / EHFH03S18D3V + cooling kit

Model name	ERLA03DV / EHFH03S18D3V + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water**EN 16147 | Average Climate**

Declared load profile	L
Efficiency η_{DHW}	110 %
COP	2.67
Heating up time	1:40 h:min
Standby power input	19 W
Reference hot water temperature	52.7 °C
Mixed water at 40°C	240 l

Model ERLA03DV / EHFZ03S18D3V

Model name	ERLA03DV / EHFZ03S18D3V
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	110 %
COP	2.67
Heating up time	1:40 h:min
Standby power input	19 W
Reference hot water temperature	52.7 °C
Mixed water at 40°C	240 l

Model ERLA03DV / EHFZ03S18D3V + cooling kit

Model name	ERLA03DV / EHFZ03S18D3V + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	110 %
COP	2.67
Heating up time	1:40 h:min
Standby power input	19 W
Reference hot water temperature	52.7 °C
Mixed water at 40°C	240 l