

Subtype DC Inverter Heat Pump 120S		
Certificate Holder	GZ Dotels Electric Appliances Co., Ltd.	
Address	No.B23, Huachuang Animation Industrial Park	
ZIP		
City	Guangzhou	
Country	CN	
Certification Body	BRE Global Limited	
Subtype title	DC Inverter Heat Pump 120S	
Registration number	041-K030-09	
Heat Pump Type	Outdoor Air/Water	
Refrigerant	R32	
Mass of Refrigerant	1.32 kg	
Certification Date	06.02.2023	
Testing basis	Heat Pump Keymark Scheme Rules Rev 11	



Model NS 120W/ENOSDI		
Model name	KS-120W/EN8SBP	
Application	Heating (medium temp)	
Units	Outdoor	
Climate zone (for heating)	n/a	
Reversibility	Yes	
Cooling mode application (optional)	n/a	
Any additional heat sources	n/a	
General data		
Power supply	3x400V 50Hz	
Off-peak product	n/a	
Outdoor Air/Water		
EN 14511-4 Heating		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	
Starting and operating test	passed	
EN 12102-1 Average Climate		
Sound power level outdoor	Low temperature 61 dB(A)	Medium temperature 65 dB(A)
EN 14825 Average Climate		
	Low tomporature	Madium tomporatura
	Low temperature 177 %	Medium temperature
ηs Prated	11.31 kW	11.13 kW
Flated	II.JI KW	
SCOD	4 40	
SCOP	4.49 7.°C	3.38
Tbiv	-7 °C	3.38 -7 °C
Tbiv TOL	-7 °C -10 °C	3.38 -7 °C -10 °C
Tbiv TOL Pdh Tj = -7°C	-7 °C -10 °C 10.00 kW	3.38 -7 °C -10 °C 9.84 kW
Tbiv TOL Pdh Tj = -7°C COP Tj = -7°C	-7 °C -10 °C 10.00 kW 2.58	3.38 -7 °C -10 °C 9.84 kW 2.02
Tbiv TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C	-7 °C -10 °C 10.00 kW 2.58 0.990	3.38 -7 °C -10 °C 9.84 kW 2.02 0.990
Tbiv TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C	-7 °C -10 °C 10.00 kW 2.58 0.990 6.10 kW	3.38 -7 °C -10 °C 9.84 kW 2.02 0.990 6.48 kW
Tbiv TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C	-7 °C -10 °C 10.00 kW 2.58 0.990 6.10 kW 4.16	3.38 -7 °C -10 °C 9.84 kW 2.02 0.990 6.48 kW 3.15
Tbiv TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C	-7 °C -10 °C 10.00 kW 2.58 0.990 6.10 kW 4.16 0.990	3.38 -7 °C -10 °C 9.84 kW 2.02 0.990 6.48 kW 3.15 0.990
Tbiv TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C	-7 °C -10 °C 10.00 kW 2.58 0.990 6.10 kW 4.16 0.990 4.30 kW	3.38 -7 °C -10 °C 9.84 kW 2.02 0.990 6.48 kW 3.15 0.990 4.51 kW
Tbiv TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C	-7 °C -10 °C 10.00 kW 2.58 0.990 6.10 kW 4.16 0.990 4.30 kW 6.63	3.38 -7 °C -10 °C 9.84 kW 2.02 0.990 6.48 kW 3.15 0.990 4.51 kW 4.70
Tbiv TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C	-7 °C -10 °C 10.00 kW 2.58 0.990 6.10 kW 4.16 0.990 4.30 kW	3.38 -7 °C -10 °C 9.84 kW 2.02 0.990 6.48 kW 3.15 0.990 4.51 kW
Tbiv TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C Pdh Tj = $+7^{\circ}$ C	-7 °C -10 °C 10.00 kW 2.58 0.990 6.10 kW 4.16 0.990 4.30 kW 6.63	3.38 -7 °C -10 °C 9.84 kW 2.02 0.990 6.48 kW 3.15 0.990 4.51 kW 4.70
Tbiv TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C	-7 °C -10 °C 10.00 kW 2.58 0.990 6.10 kW 4.16 0.990 4.30 kW 6.63 0.990	3.38 -7 °C -10 °C 9.84 kW 2.02 0.990 6.48 kW 3.15 0.990 4.51 kW 4.70 0.990
Tbiv TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C Pdh Tj = $+7^{\circ}$ C Pdh Tj = $+7^{\circ}$ C	-7 °C -10 °C 10.00 kW 2.58 0.990 6.10 kW 4.16 0.990 4.30 kW 6.63 0.990 5.14 kW	3.38 -7 °C -10 °C 9.84 kW 2.02 0.990 6.48 kW 3.15 0.990 4.51 kW 4.70 0.990 5.02 kW
Tbiv TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C Pdh Tj = 12° C Pdh Tj = 12° C	-7 °C -10 °C 10.00 kW 2.58 0.990 6.10 kW 4.16 0.990 4.30 kW 6.63 0.990 5.14 kW	3.38 -7 °C -10 °C 9.84 kW 2.02 0.990 6.48 kW 3.15 0.990 4.51 kW 4.70 0.990 5.02 kW 7.16



Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	9.88 kW	9.97 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.49	1.89
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.990	0.990
WTOL	65 °C	65 °C
Poff	12 W	12 W
РТО	30 W	30 W
PSB	12 W	12 W
РСК	25 W	25 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	1.42 kW	1.16 kW
Annual energy consumption Qhe	5201 kWh	6802 kWh