

Subtype Monobloc Air-to-Water Heat Pump System- R32- U162			
Certificate Holder Address	Qingdao Haier Air Conditioner Electric Co., Ltd. Haier Development Zone Industrial Park, Economic Development Zone, Qingdao City,		
ZIP			
City	Shandong Province		
Country	CN		
Certification Body	BRE Global Limited		
Subtype title	Monobloc Air-to-Water Heat Pump System- R32- U162		
Registration number	041-K073-04		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R32		
Mass of Refrigerant	2.6 kg		
Certification Date	06.11.2023		
Testing basis	Heat Pump Keymark Scheme Rules Rev 12		



Model AU162FYCRA(HW)

Model name	AU162FYCRA(HW)	
Application	Heating (medium temp)	
Units	Outdoor	
Climate zone (for heating)	n/a	
Reversibility	Yes	
Cooling mode application (optional)	n/a	
Any additional heat sources	n/a	
General data		
Power supply	1x230V 50Hz	
Off-peak product	n/a	
Outdoor Air/Water		
EN 14511-4 Heating		
Shutting off the heat transfer medium flow	passed	
Complete power supply failure	passed	
Defrost test	passed	
Starting and operating test	passed	
EN 12102-1 Average Climate		
	Low temperature	Medium temperature
Sound power level outdoor	68 dB(A)	72 dB(A)
EN 14825 Average Climate		
	Low temperature	Medium temperature
ηs	161 %	119 %
Prated	16.00 kW	13.92 kW
SCOP	4.10	3.05
Tbiv		
Tbiv TOL	-7 °C	-7 °C
TOL	-7 °C -25 °C	-7 °C -25 °C
TOL Pdh Tj = -7°C	-7 °C -25 °C 14.15 kW	-7 °C -25 °C 12.31 kW
TOL Pdh Tj = -7°C COP Tj = -7°C	-7 °C -25 °C 14.15 kW 2.73	-7 °C -25 °C 12.31 kW 1.78
TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C	-7 °C -25 °C 14.15 kW 2.73 0.900	-7 °C -25 °C 12.31 kW 1.78 0.900
TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C	-7 °C -25 °C 14.15 kW 2.73 0.900 8.75 kW	-7 °C -25 °C 12.31 kW 1.78 0.900 7.69 kW
TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C	-7 °C -25 °C 14.15 kW 2.73 0.900 8.75 kW 3.86	-7 °C -25 °C 12.31 kW 1.78 0.900 7.69 kW 3.08
TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C	-7 °C -25 °C 14.15 kW 2.73 0.900 8.75 kW 3.86 0.900	-7 °C -25 °C 12.31 kW 1.78 0.900 7.69 kW 3.08 0.900
TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C	-7 °C -25 °C 14.15 kW 2.73 0.900 8.75 kW 3.86 0.900 5.78 kW	-7 °C -25 °C 12.31 kW 1.78 0.900 7.69 kW 3.08 0.900 4.63 kW
TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C	-7 °C -25 °C 14.15 kW 2.73 0.900 8.75 kW 3.86 0.900 5.78 kW 5.78	-7 °C -25 °C 12.31 kW 1.78 0.900 7.69 kW 3.08 0.900 4.63 kW 4.01
TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C	-7 °C -25 °C 14.15 kW 2.73 0.900 8.75 kW 3.86 0.900 5.78 kW 5.78 0.900	-7 °C -25 °C 12.31 kW 1.78 0.900 7.69 kW 3.08 0.900 4.63 kW 4.01 0.900
TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C Pdh Tj = $+7^{\circ}$ C Pdh Tj = $+2^{\circ}$ C	-7 °C -25 °C 14.15 kW 2.73 0.900 8.75 kW 3.86 0.900 5.78 kW 5.78 0.900 5.78 kW	-7 °C -25 °C 12.31 kW 1.78 0.900 7.69 kW 3.08 0.900 4.63 kW 4.01 0.900 5.25 kW
TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C Cdh Tj = $+7^{\circ}$ C Pdh Tj = 12° C Pdh Tj = 12° C	-7 °C -25 °C 14.15 kW 2.73 0.900 8.75 kW 3.86 0.900 5.78 kW 5.78 0.900 5.09 kW 6.12	-7 °C -25 °C 12.31 kW 1.78 0.900 7.69 kW 3.08 0.900 4.63 kW 4.01 0.900 5.25 kW 6.39
TOL Pdh Tj = -7° C COP Tj = -7° C Cdh Tj = -7° C Pdh Tj = $+2^{\circ}$ C COP Tj = $+2^{\circ}$ C Cdh Tj = $+2^{\circ}$ C Pdh Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C COP Tj = $+7^{\circ}$ C Pdh Tj = $+7^{\circ}$ C Pdh Tj = $+2^{\circ}$ C	-7 °C -25 °C 14.15 kW 2.73 0.900 8.75 kW 3.86 0.900 5.78 kW 5.78 0.900 5.78 kW	-7 °C -25 °C 12.31 kW 1.78 0.900 7.69 kW 3.08 0.900 4.63 kW 4.01 0.900 5.25 kW



Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	13.35 kW	7.96 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.46	1.13
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.900	0.900
WTOL	55 °C	55 °C
Poff	5 W	5 W
РТО	59 W	59 W
PSB	5 W	5 W
РСК	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	2.65 kW	5.95 kW
Annual energy consumption Qhe	8071 kWh	9441 kWh