

Subtype EH200Pro	
Certificate Holder	Climer
Address	Carr. Córdoba - Málaga, Km. 77
ZIP	14900
City	Córdoba
Country	ES
Certification Body	SZU - Strojirensky zkusebni ustav (Engineering Test Institute, Public Enterprise)
Subtype title	EH200Pro
Registration number	037-0156-24
Heat Pump Type	Heat Pump for Domestic Hot Water (DHW)
Refrigerant	R290
Mass of Refrigerant	0.15 kg
Certification Date	27.03.2024
Testing basis	HP Keymark scheme rules rev. no. 11

**Model EH200P 444**

Model name	EH200P 444
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

**General data**

Power supply	1x230V 50Hz
Off-peak product	Yes

**Heat Pump for Domestic Hot Water (DHW)**

**EN 16147 | Operating test**

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

**EN 12102-2 | Average Climate**

Sound power level indoor	55 dB(A)
--------------------------	----------

**EN 16147 | Average Climate**

Declared load profile	L
Efficiency $\eta_{DHW}$	123 %
COP	2.95
Heating up time	6:12 h:min
Standby power input	30.5 W
Reference hot water temperature	51.8 °C
Mixed water at 40°C	210 l

**Model EH200P 2205**

Model name	EH200P 2205
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

**General data**

Power supply	1x230V 50Hz
Off-peak product	Yes

**Heat Pump for Domestic Hot Water (DHW)**

**EN 16147 | Operating test**

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

**EN 12102-2 | Average Climate**

Sound power level indoor	55 dB(A)
--------------------------	----------

**EN 16147 | Average Climate**

Declared load profile	L
Efficiency $\eta_{DHW}$	123 %
COP	2.95
Heating up time	6:12 h:min
Standby power input	30.5 W
Reference hot water temperature	51.8 °C
Mixed water at 40°C	210 l

**Model EH200P RF 444**

Model name	EH200P RF 444
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

**General data**

Power supply	1x230V 50Hz
Off-peak product	Yes

**Heat Pump for Domestic Hot Water (DHW)**

**EN 16147 | Operating test**

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

**EN 12102-2 | Average Climate**

Sound power level indoor	55 dB(A)
--------------------------	----------

**EN 16147 | Average Climate**

Declared load profile	L
Efficiency $\eta_{DHW}$	123 %
COP	2.95
Heating up time	6:12 h:min
Standby power input	30.5 W
Reference hot water temperature	51.8 °C
Mixed water at 40°C	210 l

**Model EH200P RF 2205**

Model name	EH200P RF 2205
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

**General data**

Power supply	1x230V 50Hz
Off-peak product	Yes

**Heat Pump for Domestic Hot Water (DHW)**

**EN 16147 | Operating test**

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

**EN 12102-2 | Average Climate**

Sound power level indoor	55 dB(A)
--------------------------	----------

**EN 16147 | Average Climate**

Declared load profile	L
Efficiency $\eta_{DHW}$	123 %
COP	2.95
Heating up time	6:12 h:min
Standby power input	30.5 W
Reference hot water temperature	51.8 °C
Mixed water at 40°C	210 l

**Model EH200P-BT50 444**

Model name	EH200P-BT50 444
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

**General data**

Power supply	1x230V 50Hz
Off-peak product	Yes

**Heat Pump for Domestic Hot Water (DHW)**

**EN 16147 | Operating test**

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

**EN 12102-2 | Average Climate**

Sound power level indoor	55 dB(A)
--------------------------	----------

**EN 16147 | Average Climate**

Declared load profile	L
Efficiency $\eta_{DHW}$	123 %
COP	2.95
Heating up time	6:12 h:min
Standby power input	30.5 W
Reference hot water temperature	51.8 °C
Mixed water at 40°C	210 l

**Model EH200P-BT50 2205**

Model name	EH200P-BT50 2205
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

**General data**

Power supply	1x230V 50Hz
Off-peak product	Yes

**Heat Pump for Domestic Hot Water (DHW)**

**EN 16147 | Operating test**

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

**EN 12102-2 | Average Climate**

Sound power level indoor	55 dB(A)
--------------------------	----------

**EN 16147 | Average Climate**

Declared load profile	L
Efficiency $\eta_{DHW}$	123 %
COP	2.95
Heating up time	6:12 h:min
Standby power input	30.5 W
Reference hot water temperature	51.8 °C
Mixed water at 40°C	210 l