

Climer
Carr. Córdoba - Málaga, Km. 77
14900
Córdoba
ES
SZU - Strojirensky zkusebni ustav (Engineering Test Institute, Public Enterprise)
EH160Pro
037-0155-24
Heat Pump for Domestic Hot Water (DHW)
R290
0.15 kg
27.03.2024
HP Keymark scheme rules rev. no. 11



Model EH160P 444	
Model name	EH160P 444
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a
General data	
Power supply	1x230V 50Hz
Off-peak product	Yes
Heat Pump for Domestic Hot Water (DHW EN 16147 Operating test	V)
Temperature operating range	2
Safety devices checking test	2
Condensate draining	2
EN 12102-2 Average Climate	
Sound power level indoor	55 dB(A)
EN 16147 Average Climate	
Declared load profile	M
Efficiency ηDHW	108 %
COP	2.56
Heating up time	5:51 h:min
Standby power input	21.0 W
Reference hot water temperature	51.5 °C
Mixed water at 40°C	169



Model EH160P 2205	
Model name	EH160P 2205
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a
General data	
Power supply	1x230V 50Hz
Off-peak product	Yes
Heat Pump for Domestic Hot Water (DHW) EN 16147 Operating test	
	2
Temperature operating range Safety devices checking test	2
Condensate draining	2
Condensate draining	Z
EN 12102-2 Average Climate	
Sound power level indoor	55 dB(A)
EN 16147 Average Climate	
Declared load profile	M
Efficiency ηDHW	108 %
COP	2.56
Heating up time	5:51 h:min
Standby power input	21.0 W
Reference hot water temperature	51.5 °C
Mixed water at 40°C	169 l



Model EH160P RF 444	
Model name	EH160P RF 444
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a
General data	
Power supply	n/a
Off-peak product	n/a
Heat Pump for Domestic Hot Water (DHW)	
EN 16147 Operating test	
Temperature operating range	2
Safety devices checking test	2
Condensate draining	2
EN 12102-2 Average Climate	
Sound power level indoor	55 dB(A)
EN 16147 Average Climate	
Declared load profile	M
Efficiency ηDHW	108 %
СОР	2.56
Heating up time	5:51 h:min
Standby power input	21.0 W
Reference hot water temperature	51.5 °C
Mixed water at 40°C	169



Model EH160P RF 2205	
Model name	EH160P RF 2205
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a
General data	
Power supply	1x230V 50Hz
Off-peak product	Yes
Heat Pump for Domestic Hot Water (DHW) EN 16147 Operating test	
Temperature operating range	2
Safety devices checking test	2
Condensate draining	Z
EN 12102-2 Average Climate	
Sound power level indoor	55 dB(A)
EN 16147 Average Climate	
Declared load profile	M
Efficiency ηDHW	108 %
СОР	2.56
Heating up time	5:51 h:min
Standby power input	21.0 W
Reference hot water temperature	51.5 °C
Mixed water at 40°C	169 l