

Subtype Riello DOMUS T 11T AIO

Certificate Holder	Riello S.p.A.
Address	Via Ing. Pilade Riello 7
ZIP	37045
City	Legnago (VR)
Country	IT
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH
Subtype title	Riello DOMUS T 11T AIO
Registration number	011-1W0721
Heat Pump Type	Outdoor Air/Water
Refrigerant	R32
Mass of Refrigerant	1.3 kg
Certification Date	24.10.2023
Testing basis	HP KEYMARK certification scheme rules V12

Model HP ODU SPRINT 11T / HP IDU DOMUS M31AM

Model name	HP ODU SPRINT 11T / HP IDU DOMUS M31AM
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	135 %
COP	3.03
Heating up time	0:42 h:min
Standby power input	35 W
Reference hot water temperature	47.7 °C
Mixed water at 40°C	235 l

Model HP ODU SPRINT 11T / HP IDU DOMUS M61AM

Model name	HP ODU SPRINT 11T / HP IDU DOMUS M61AM
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water**EN 16147 | Average Climate**

Declared load profile	XL
Efficiency η_{DHW}	135 %
COP	3.03
Heating up time	0:42 h:min
Standby power input	35 W
Reference hot water temperature	47.7 °C
Mixed water at 40°C	235 l

Model HP ODU SPRINT 11T / HP IDU DOMUS T61AM

Model name	HP ODU SPRINT 11T / HP IDU DOMUS T61AM
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	135 %
COP	3.03
Heating up time	0:42 h:min
Standby power input	35 W
Reference hot water temperature	47.7 °C
Mixed water at 40°C	235 l

Model HP ODU SPRINT 11T / HP IDU DOMUS M32AM

Model name	HP ODU SPRINT 11T / HP IDU DOMUS M32AM
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	135 %
COP	3.03
Heating up time	0:42 h:min
Standby power input	35 W
Reference hot water temperature	47.7 °C
Mixed water at 40°C	235 l

Model HP ODU SPRINT 11T / HP IDU DOMUS M62AM

Model name	HP ODU SPRINT 11T / HP IDU DOMUS M62AM
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	135 %
COP	3.03
Heating up time	0:42 h:min
Standby power input	35 W
Reference hot water temperature	47.7 °C
Mixed water at 40°C	235 l

Model HP ODU SPRINT 11T / HP IDU DOMUS T62AM

Model name	HP ODU SPRINT 11T / HP IDU DOMUS T62AM
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	135 %
COP	3.03
Heating up time	0:42 h:min
Standby power input	35 W
Reference hot water temperature	47.7 °C
Mixed water at 40°C	235 l