

Subtype DAIKIN ALTHERMA H ECH2O / ROTEX HPSU MONOBLOC COMPACT 5KW (500L)

Certificate Holder	DAIKIN Europe N.V.
Address	Zandvoordestraat 300
ZIP	B-8400
City	Oostende
Country	BE
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH
Subtype title	DAIKIN ALTHERMA H ECH2O / ROTEX HPSU MONOBLOC COMPACT 5KW (500L)
Registration number	011-1W0269
Heat Pump Type	Outdoor Air/Water
Refrigerant	R410A
Mass of Refrigerant	1.3 kg

Model RBLQ05C2V3 / RKHWMXB500C

Model name	RBLQ05C2V3 / RKHWMXB500C
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	No

Outdoor Air/Water**EN 16147 | Average Climate**

Declared load profile	XL
Efficiency η_{DHW}	99 %
COP	2.41
Heating up time	3:05 h:min
Standby power input	39.0 W
Reference hot water temperature	48.0 °C
Mixed water at 40°C	211 l

Model RBLQ05C2V3 / RKHWMX500C

Model name	RBLQ05C2V3 / RKHWMX500C
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	No

Outdoor Air/Water**EN 16147 | Average Climate**

Declared load profile	XL
Efficiency η_{DHW}	102 %
COP	2.48
Heating up time	3:05 h:min
Standby power input	39.0 W
Reference hot water temperature	48.0 °C
Mixed water at 40°C	237 l

Model EBLQ05C2V3 / EKHWMXB500C

Model name	EBLQ05C2V3 / EKHWMXB500C
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	No

Outdoor Air/Water**EN 16147 | Average Climate**

Declared load profile	XL
Efficiency η_{DHW}	99 %
COP	2.41
Heating up time	3:05 h:min
Standby power input	39.0 W
Reference hot water temperature	48.0 °C
Mixed water at 40°C	211 l

Model EBLQ05C2V3 / EKHWMX500C

Model name	EBLQ05C2V3 / EKHWMX500C
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	No

Outdoor Air/Water**EN 16147 | Average Climate**

Declared load profile	XL
Efficiency η_{DHW}	102 %
COP	2.48
Heating up time	3:05 h:min
Standby power input	39.0 W
Reference hot water temperature	48.0 °C
Mixed water at 40°C	237 l