

Subtype DAIKIN ALTHERMA 3 H HT F 14KW (230L)

Certificate Holder	DAIKIN Europe N.V.
Address	Zandvoordestraat 300
ZIP	B-8400
City	Oostende
Country	BE
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH
Subtype title	DAIKIN ALTHERMA 3 H HT F 14KW (230L)
Registration number	011-1W0354
Heat Pump Type	Outdoor Air/Water
Refrigerant	R32
Mass of Refrigerant	4.2 kg
Certification Date	07.02.2020

Model EPRA14DV3 / ETVH16S23E(6V/9W)

Model name	EPRA14DV3 / ETVH16S23E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	108 %
COP	2.61
Heating up time	1:19 h:min
Standby power input	49.2 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DW1 / ETVH16S23E(6V/9W)

Model name	EPRA14DW1 / ETVH16S23E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	3x400V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	107 %
COP	2.55
Heating up time	1:19 h:min
Standby power input	58.5 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DV3 / ETVX16S23E(6V/9W)

Model name	EPRA14DV3 / ETVX16S23E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	108 %
COP	2.61
Heating up time	1:19 h:min
Standby power input	49.2 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DW1 / ETVX16S23E(6V/9W)

Model name	EPRA14DW1 / ETVX16S23E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	3x400V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	107 %
COP	2.55
Heating up time	1:19 h:min
Standby power input	58.5 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DV3 / ETVZ16S23E(6V/9W)

Model name	EPRA14DV3 / ETVZ16S23E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	108 %
COP	2.61
Heating up time	1:19 h:min
Standby power input	49.2 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DW1 / ETVZ16S23E(6V/9W)

Model name	EPRA14DW1 / ETVZ16S23E(6V/9W)
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	3x400V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	107 %
COP	2.55
Heating up time	1:19 h:min
Standby power input	58.5 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DV3 / ETVH16S23E(6V/9W) + cooling kit

Model name	EPRA14DV3 / ETVH16S23E(6V/9W) + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	108 %
COP	2.61
Heating up time	1:19 h:min
Standby power input	49.2 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DW1 / ETVH16S23E(6V/9W) + cooling kit

Model name	EPRA14DW1 / ETVH16S23E(6V/9W) + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	3x400V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	107 %
COP	2.55
Heating up time	1:19 h:min
Standby power input	58.5 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DV3 / ETVH16SU23E6V

Model name	EPRA14DV3 / ETVH16SU23E6V
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	108 %
COP	2.61
Heating up time	1:19 h:min
Standby power input	49.2 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DW1 / ETVH16SU23E6V

Model name	EPRA14DW1 / ETVH16SU23E6V
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	3x400V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	107 %
COP	2.55
Heating up time	1:19 h:min
Standby power input	58.5 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DV37 / ETVH16S23E(6V/9W)7

Model name	EPRA14DV37 / ETVH16S23E(6V/9W)7
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	108 %
COP	2.61
Heating up time	1:19 h:min
Standby power input	49.2 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DW17 / ETVH16S23E(6V/9W)7

Model name	EPRA14DW17 / ETVH16S23E(6V/9W)7
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	3x400V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	107 %
COP	2.55
Heating up time	1:19 h:min
Standby power input	58.5 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DV37 / ETVH16SU23E6V7

Model name	EPRA14DV37 / ETVH16SU23E6V7
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	108 %
COP	2.61
Heating up time	1:19 h:min
Standby power input	49.2 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DW17 / ETVH16SU23E6V7

Model name	EPRA14DW17 / ETVH16SU23E6V7
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	3x400V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	107 %
COP	2.55
Heating up time	1:19 h:min
Standby power input	58.5 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DV37 / ETVX16S23E(6V/9W)7

Model name	EPRA14DV37 / ETVX16S23E(6V/9W)7
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	108 %
COP	2.61
Heating up time	1:19 h:min
Standby power input	49.2 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DW17 / ETVX16S23E(6V/9W)7

Model name	EPRA14DW17 / ETVX16S23E(6V/9W)7
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	3x400V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	107 %
COP	2.55
Heating up time	1:19 h:min
Standby power input	58.5 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DV37 / ETVZ16S23E(6V/9W)7

Model name	EPRA14DV37 / ETVZ16S23E(6V/9W)7
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	108 %
COP	2.61
Heating up time	1:19 h:min
Standby power input	49.2 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DW17 / ETVZ16S23E(6V/9W)7

Model name	EPRA14DW17 / ETVZ16S23E(6V/9W)7
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	3x400V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	107 %
COP	2.55
Heating up time	1:19 h:min
Standby power input	58.5 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DV37 / ETVH16S23E(6V/9W)7 + cooling kit

Model name	EPRA14DV37 / ETVH16S23E(6V/9W)7 + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	108 %
COP	2.61
Heating up time	1:19 h:min
Standby power input	49.2 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l

Model EPRA14DW17 / ETVH16S23E(6V/9W)7 + cooling kit

Model name	EPRA14DW17 / ETVH16S23E(6V/9W)7 + cooling kit
Application	Heating + DHW + low temp
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Reversibility	Yes
Cooling mode application (optional)	+7°C/12°C
Any additional heat sources	n/a

General data

Power supply	3x400V 50Hz
Off-peak product	n/a

Outdoor Air/Water

EN 16147 | Average Climate

Declared load profile	XL
Efficiency η_{DHW}	107 %
COP	2.55
Heating up time	1:19 h:min
Standby power input	58.5 W
Reference hot water temperature	52.5 °C
Mixed water at 40°C	298 l