

Subtype ECL-BT-200

Certificate Holder	ECL Nexus
Address	13, Boulevard Pereire
ZIP	75017
City	Paris
Country	FR
Certification Body	ICIM S.p.A.
Subtype title	ECL-BT-200
Registration number	ICIM-PDC-000147
Heat Pump Type	Heat Pump for Domestic Hot Water (DHW)
Refrigerant	R134a
Mass of Refrigerant	0.92 kg
Certification Date	20.05.2022
Testing basis	V8

Model ECLBT200X.01	
Model name	ECLBT200X.01
Application	Heating + DHW
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a
General data	
Power supply	1x230V 50Hz
Off-peak product	No
Heat Pump for Domestic Hot Water (DHW)	
EN 16147 Operating test	
Temperature operating range	2
Safety devices checking test	2
Condensate draining	2
EN 12102-2 Average Climate	
Sound power level indoor	58 dB(A)
EN 16147 Average Climate	
Declared load profile	L
Efficiency η_{DHW}	111 %
COP	2.64
Heating up time	7:48 h:min
Standby power input	40.0 W
Reference hot water temperature	55.0 °C
Mixed water at 40°C	291 l

Model ECLBT200S.01

Model name	ECLBT200S.01
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	No

Heat Pump for Domestic Hot Water (DHW)

EN 16147 | Operating test

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

EN 12102-2 | Average Climate

Sound power level indoor	58 dB(A)
--------------------------	----------

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	111 %
COP	2.64
Heating up time	7:48 h:min
Standby power input	40.0 W
Reference hot water temperature	55.0 °C
Mixed water at 40°C	291 l

Model ECLBT200D.01

Model name	ECLBT200D.01
Application	n/a
Units	Indoor
Climate zone (for heating)	n/a
Heat Source	Outdoor Air
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	1x230V 50Hz
Off-peak product	No

Heat Pump for Domestic Hot Water (DHW)

EN 16147 | Operating test

Temperature operating range	2
Safety devices checking test	2
Condensate draining	2

EN 12102-2 | Average Climate

Sound power level indoor	58 dB(A)
--------------------------	----------

EN 16147 | Average Climate

Declared load profile	L
Efficiency η_{DHW}	111 %
COP	2.64
Heating up time	7:48 h:min
Standby power input	40.0 W
Reference hot water temperature	55.0 °C
Mixed water at 40°C	291 l